


Site 1

Luminaire layout plan




Manufacturer	Noch kein DIALux Mitglied	P	5.0 W
Article name		$\Phi_{\text{Luminaire}}$	1000 lm
Fitting	1x		

Individual luminaires

X	Y	Mounting height	Luminaire
69.002 m	34.610 m	4.850 m	3
69.604 m	33.113 m	4.850 m	4
35.674 m	21.623 m	4.850 m	5
36.278 m	20.124 m	4.850 m	6

Site 1

Luminaire layout plan



Manufacturer	Noch kein DIALux Mitglied
Article name	
Fitting	1x

P	10.0 W
$\Phi_{\text{Luminaire}}$	2000 lm

Individual luminaires

X	Y	Mounting height	Luminaire
145.400 m	62.900 m	4.850 m	1
110.700 m	50.100 m	4.850 m	2


Site 1

Luminaire list

Φ_{total}	P_{total}	Luminous efficacy
8000 lm	40.0 W	200.0 lm/W

pcs.	Manufacturer	Article No.	Article name	P	Φ	Luminous efficacy
4	Noch kein DIALux Mitglied			5.0 W	1000 lm	200.0 lm/W
2	Noch kein DIALux Mitglied			10.0 W	2000 lm	200.0 lm/W

Site 1 (Light scene 1)

Calculation objects

Site 1 (Light scene 1)

Calculation objects


Calculation surfaces

Properties	E	E _{min}	E _{max}	U _o (g ₁)	g ₂	Index
Calculation surface 16 Perpendicular illuminance Height: 0.000 m	2.63 lx	0.00 lx	19.1 lx	0.00	0.00	CG1

Utilisation profile: DIALux presetting (5.1.4 Standard (outdoor transportation area))

Site 1 (Light scene 1)

Calculation surface 16



Properties	\bar{E}	E_{min}	E_{max}	$U_o (g_1)$	g_2	Index
Calculation surface 16 Perpendicular illuminance Height: 0.000 m	2.63 lx	0.00 lx	19.1 lx	0.00	0.00	CG1

Utilisation profile: DIALux presetting (5.1.4 Standard (outdoor transportation area))