


Site 1

## Luminaire layout plan



Manufacturer	Noch kein DIALux Mitglied	P	8.0 W
Article name		$\Phi_{\text{Luminaire}}$	1600 lm
Fitting	1x		

### Individual luminaires

X	Y	Mounting height	Luminaire
7.464 m	261.014 m	4.850 m	1
60.640 m	234.531 m	4.850 m	2
113.526 m	207.807 m	4.850 m	3
166.686 m	181.155 m	4.850 m	4
219.600 m	154.600 m	4.850 m	5
273.128 m	127.507 m	4.850 m	6
331.056 m	98.671 m	4.850 m	7
397.845 m	65.904 m	4.850 m	8
464.007 m	33.619 m	4.850 m	9


Site 1

## Luminaire list

$\Phi_{\text{total}}$	$P_{\text{total}}$	Luminous efficacy
14400 lm	72.0 W	200.0 lm/W

pcs.	Manufacturer	Article No.	Article name	P	$\Phi$	Luminous efficacy
9	Noch kein DIALux Mitglied			8.0 W	1600 lm	200.0 lm/W

Site 1 (Light scene 1)

**Calculation objects**

Site 1 (Light scene 1)


**Calculation objects**

## Calculation surfaces

Properties	E	E <sub>min</sub>	E <sub>max</sub>	U <sub>0</sub> (g <sub>1</sub> )	g <sub>2</sub>	Index
Calculation surface 15 Perpendicular illuminance Height: 0.000 m	1.60 lx	0.041 lx	9.94 lx	0.026	0.004	CG1

Utilisation profile: DIALux presetting (5.1.4 Standard (outdoor transportation area))

Site 1 (Light scene 1)

**Calculation surface 15**

Properties	$\bar{E}$	$E_{min}$	$E_{max}$	$U_o (g_1)$	$g_2$	Index
Calculation surface 15 Perpendicular illuminance Height: 0.000 m	1.60 lx	0.041 lx	9.94 lx	0.026	0.004	CG1

Utilisation profile: DIALux presetting (5.1.4 Standard (outdoor transportation area))

