


The diagram illustrates a road cross-section with the following dimensions and labels:

- Left side (from left to right):**
  - 100 (width of the left shoulder)
  - 200 (width of the left lane)
  - 225 (width of the left lane)
- Right side (from right to left):**
  - 200 (width of the right lane)
  - 225 (width of the right lane)
  - 75 (width of the right shoulder)
- Central section (from left to right):**
  - 75 (width of the left shoulder)
  - 200 (width of the left lane)
  - 200 (width of the right lane)
  - 75 (width of the right shoulder)
- Labels and Markers:**
  - linia rozgraniczająca** (dividing line) at the far left and far right.
  - pobocze** (shoulder) above the 75 dimensions.
  - jezdnia** (lane) above the 200 dimensions.
  - 400** (total lane width) below the central 200+200 section.
  - A** (arrow pointing up) above the central section.



skarpy i dno rowu umocnione kamieniem narzutowym  
(polnym) 16-20 cm na suchym betonie C15/20,  
spoiny wypełnione zaprawą cementową

80

400

**Przekrój A-A**

180.30

80

178.92

100

25, 25, 25

1:1.5

75

40 80 40

160

bepośrednio przy rurze (0,2 m)  
zastosować mieszankę niezwiązaną  
z kruszywem 0-20 mm

podsyпка wspierająca z mieszanek  
niezwiązanej z kruszywem 0-20 mm

13